

背面

LEADTEK

NetWork
Care Phone NCP3680

Hardware Configuration

- > Camera Unit: CMOS, 1.3Mega pixel
- > RJ-45 LAN : 10 /100 Ethernet
- > Built-in microphone
- > Terminal Block : 1DO
- > Embed Speaker Output 1W (85.4 db)
- > DC Jack :DC5V power input
- > Tack switches: System reset , Restore factory default

NETWORKING

Ethernet: 10/100BaseT Ethernet
Protocol: TCP/IP, DHCP, PPPoE, HTTP, SMTP, FTP, RTSP,
RTP/RTCP, TFTP, SIP, DDNS
Network Bandwidth: 128k/256k/384k/512k/768k/1M/1.5M/2M

Video Setting and Performance

Compression: MPEG-4 SP
Frame Rate : 1 to 30
Quality : Adaptive

Adjustable Resolution (MPEG4):

Up to 15fps@720x480 (D1)
Up to 30fps@ 640x480 (VGA)
Up to 30fps @ 352x288 (CIF)
Up to 30fps @ 176 x 144(QCIF)

Adjustable Resolution (H.263):

Up to 30fps @ 352x288 (CIF)
Up to 30fps @ 176 x 144(QCIF)

Audio Setting

Codec : G.711 (a-law / mu-law)
Transmission : Two-way communication by SIP signaling,
Half-duplex

EVENT CONTROL

Event Types : Motion detection, Scheduler, Manual Snapshot
and Alarm-in
Motion Detection : Sensitivity control
Event Action : Send snapshots via FTP or Email in JPEG
format (640x480)



SECURITY

User Management: Administrator and User group privileged
protection
Authentication: ID and password protection
Site Demonstration: Guess account with privilege limitation

ENVIRONMENT

Operation Temperature : 0 ~ 50°C (tentative)
Operation Humidity : < 85%, non-condensing

Advance Feature

Windows based Soft-phone and recording software bundled

Minimum System Requirements for Surveillance Software

CPU : Intel Pentium IV 2GHz or above
System RAM : 512MB or above
OS : Microsoft Windows 2000 with Service Pack 6 , XP Home /
Professional with SP 2
Sound Card : 8bit full duplex, Windows compatible
Browser : Microsoft Internet Explorer 6.0
Storage : 40GB free space of hard disk drive with 7200RPM
capability



www.leadtek.com

Add : 18F 166 Chien-Yi Rd., Chung Ho City, Taipei County 23511, Taiwan
Tel : +886 2 8226 5800 Fax : +886 2 8226 5801 E-Mail : contact@leadtek.com.tw

正面

LEADTEK



WinFast® CarePhone

Feature

Communication

- > Build-in speaker and microphone for two way audio + one way video communication.
- > Internet connection compatible with Ethernet 10 /100 Base – T standard.
- > On touch bottom to establish audio / video communication with PC based soft phone via internet.

Surveillance

- > Bundled remote surveillance and management PC software
- > Support audiovisual transmission, recording and snap shot.
- > A client viewer is able to access multiple cameras locating at different sites simultaneously.

Remote Tele-care

- > With Video Phone inter-operation (2-way audio / 1-way video) for remote diagnosis

NetWork
Care Phone NCP3680

